



Main

Range of product	Sedna
Range	Sedna
Device application	Control
Product or component type	Switch
Switch function	1-pole 2-circuit
Device presentation	Without frame
Rated current	10 AX - 250 V AC
Cover plate colour tint	White
Connections - terminals	Screwless terminals

Complementary

Accessory / separate part type	Claw and screw for mechanism
Pilot light	Blue locator lamp
Power range	2300 W
Wiring device mounting	Flush
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	13 mm
Material	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Screws Screws Claws, span of claws working range : 51...70 mm
Height	71 mm
Width	71 mm
Depth	37 mm
Projecting depth	12 mm
Product weight	0.058165 kg

Environment

standards	IEC 60669-1
quality labels	CE
product certifications	GOST-R
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.