



## Main

Range of product	Sedna
Product or component type	Socket-outlet
Device presentation	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Poland
Rated current	16 A - 250 V AC
Cover plate colour tint	Aluminium
Connections - terminals	Lift terminals

## Complementary

Wiring device mounting	Flush
Power range	3680 W
Number of cables	2 x 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid
Wire stripping length	13 mm
Material	PC
Surface finish	Glossy
Fixing mode	Screws Screws Claws, span of claws working range : 52...69 mm
Height	71 mm
Width	71 mm
Depth	41.3 mm
Projecting depth	10 mm
Product weight	0.067822 kg

## Environment

standards	IEC 60884-1
product certifications	GOST-R
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.